



## AB-88D

- Classic economy design
- Easy maintenance
- Multi data interface options available

### PRODUCT FEATURES



**Big paper roll loadable**  
80 mm diameter paper roll makes printing longer and stable.



**Easy maintenance**  
Simple inner frame, module design, easy to maintain.



**Multi data interface**  
Available of LAN / USB / RS232 ports.

### SPECIFICATIONS

Printing Method	Direct Thermal	CODE PAGES SUPPORTED	PC437 / Katakana / PC850 / PC860 / PC863 / PC865 /
Resolution	8dots/mm		WPC1253 / Iran / WPC1256 / PC737 / WPC1250 /
Printing Density	640dots/line		WPC1252 / PC866 / PC852 / PC858 / Latvian / Vietnam /
Printing Speed	220mm/s		Uigur / WPC1255 Israel / WPC862 / WPC1257 /
Paper Width	72mm		WPC775 / WPC1251 / PC861 Icelandic / PC857 Turkey
Paper Type	Thermal Paper: 79.5±0.5mm Max Diameter: 80mm		/ PC874 Thai / PC3021 Bulgarian / User define
Tearing way	Auto cut	Supportable Barcode Types	JAN13(EAN13) / JAN8(EAN8) / CODE39 / CODE128 /
Sensor	Out of paper		UPC-A / UPC-E / ITF / CODABAR / CODE93
Character Size	ANK Character, Font A: 12x24, FontB: 9x17, Chinese: 24x24	Interface Options	USB+RS232,(WIFI or Bluetooth is optional)
Character Per Line	Font A: 42/48/53(EPSON Mode, adjusted via 8 DIP Switch) Font B: 56/64(Normal Mode)	Life	Printer Head:100,000,000 pulses or more,100 kilometers or more Cutter:1,000,000 cuts or more
Font Library	GBK big font library	Environmen	Work Temp. and Humidity: 0~50 C ;30~85%RH Environment Temp. and Humidity:-20~60 C ;30~85%RH
Buffer Capacity	20K	Adapter	DC24V,2.5A
Dimensiont	192.8(L)X145(W)X140.5(H)mm	Drawer Port	DC24V,1A(RJ11)
Carton Sizes	260mmX210mmX230mm inner box-80mm	Transport packing quantity	8
		Authentication information	CCC Certification / CB Certification / CE Certification / FC Ccertification

