

# Label/Sticker Printer

## AB-F820



### HIGHLIGHTS

- Support label and barcode printing
- High printing speed
- Wide range of printing size adjustable
- Popular data connection options
- Easy operation and maintenance

### APPLICATION REFERENCE

- Ideal for
- Industrial supply chain
- Goods Labeling
- Transportation and logistics
- Retail
- Public service



### SPECIFICATIONS

Printing Method	Thermal printing	Power Input	Input:AC100-240V Output:DC 24V2.5A
Resolution	8 dots/mm	Power Consumption	2.2W
Printing Speed	100mm/s max.	(standby)	
Printing Width	16-80mm	Power Rated	56W
Paper Roll	Thermal sticker paper roll: 25.14±0.5mm	Power Max.	160W
	Diameter (max.): 100mm	Lifespan	Printer Mechanism: 100,000,000 pulses or above;
Paper Tearing	Manual		50km or above
Data Buffer	4MB	Environment	Work Temp. & Humidity: 0~45°C , 35~85%RH
Barcodes	1D: Code 39,Code 93,Code128UCC,Code 128		Storage Temp. & Humidity: -10~50°C , 10~90%RH
	subset A,B,Codabar,,Interleave 2 of 5,EAN-8,	Sizes	215*145*140mm
	EAN-13,EAN-128,UPC-A,UPC-E	Net Weight	1.25KG
	2D: PDF-147,Maxicode,DataMatrix,QR Code		
Port Options	USB / RS-232		