

## ZQ-T9150



- Housing made by Aluminum
- Fanless system with BayTrail J1900 Quad Core CPU
- True flat water proof touch screen
- Easy maintance
- Various options of peripherals

### PRODUCT FEATURES

- Customer display 2X20VFD
- MSR, I-Button, RFID



Opitonal MSR



Aluminum housing



Opitonal I-button



Various interfaces

### SPECIFICATIONS

|            |  |                |   |
|------------|--|----------------|---|
| CPU        | Intel® Bay-Trail J1900 Quad Core   | O.S. Compliant | WIN7 / WIN8 / WIN10 / Linux   |
| Memory     | 2GB  | Power Supply   | 100-240V/ 3.5A 47~63Hz  |
| Network    | RTL8168DE PCI-E Gigabit Ethernet NIC   | Dimension      | 390x200x360mm(WxDxH)  |
| Video Card | Intel Graphics Media   | DISPLAY        | Viewing Angle: 85 degree adjustable   |
| Sound Card | Accelerator3150(256MB/Intel)RTL ALC662 @INTEL<br>82801G(ICH7)High Definition Audio   |                | LCD: 15" TFT LCD<br>Max. Resolution: 1024 x 768                                   |
| HDD        | 32GB SSD   |                | Touch panel: 5-wire resistive or multi-point capacitive (optional)                |
| I/O PORTS  | USB: 4 x USB 2.0 port<br>Serial Port: 3 x DB-9 RS232<br>VGA: 1 x DB-15 VGA Interface<br>LAN: 1 x 10/100/1000 Mbps<br>Audio: 1 x Output<br>Power Input: 1 | ENVIRONMENT    | Operation Temperature: 0~40℃<br>Storage Temperature: -40~50℃<br>Humidity: 38~80%℃ |

