

# Smart Android POS Terminal

## ZQ-1010

### HIGHLIGHTS

- 10.1" Capacitive touch panel
- Android system
- Built-in thermal printer
- Camera integration for option
- Muti data ports
- WiFi supported / 3G or 4G optional



### SPECIFICATIONS

CPU	Rockchip RK3066 Dual-core Cortex-A9 1.5GHZ Quad-Core GPU Mail-400	Thermal Printer	58mm Thermal Printer, Max 60 mm/sec, Diameter Max. $\varnothing$ 60 mm, USB GB2312, PC437, Katakana, PC850, PC860, PC863, PC865, WPC1253, Iran, WPC1256, PC737, WPC1250, WPC1252, PC866, PC852, PC858, , User define	
RAM	DDR3 1GB		Optional Peripherals	MSR
Storage	NAND Flash 4GB Mini SD 32GB(max) Extendable	RFID		RS232 DC5V $\pm$ 5%, 65mA (max)
WI-FI	Optional 802.11 b/g/n WI-FI module	IC Card		RS232 DC5V $\pm$ 5%, 65mA (max)
OS	Android 4.2	External Port	3 x USB, 1 x TF, 1 x LAN, 1 x DC12V Input, 1 x Cash Drawer, 1 x RS232	
Language	English /Chinese /Russian /French /German /Italian /Spanish		Camera (Optional)	0.3MP 2D Barcode scanner
Operator Display	10.1" diagonal, LED Back light, 1024 $\times$ 600, LVDS	Environment	Operating temperature and humidity: -10 $^{\circ}$ C ~ 40 $^{\circ}$ C, 20 ~ 80% RH	
Touch Screen	10.1" diagonal, Projected Capacitive touch, I2C		Storage temperature and humidity: -20 $^{\circ}$ C ~ 50 $^{\circ}$ C, 20 ~ 90% RH	
Customer Display	LED 9 Digit, DC5V, RS232, 9600BPS Characters: 0...9	Dimension	276(L) $\times$ 272 (W) $\times$ 95 (H) mm	
(optional)	LCD 2*20 Digit, DC5V, RS232, 9600BPS; ASCII code			
Power Supply	DC12V 5A			
Battery (optional)	8.4V 2200mAh			



Customer Display



Multi Ports



Camera



Capacitive Touch Panel



Color Options Available