

Omnidirectional Desktop Laser Barcode Scanner

FEATURES

- 24 scan lines in 6 scan directions at scan speed of 2000 scans/sec;
- Support all 1D barcodes including code bar GS1;
- High identification ability of damaged barcodes and substandard barcodes;
- Automatic Sleeping & Wake-up modes save power and improve lifespan;
- Modern design and compact size make the best choice for various users.



ZQ-LS7025

SPECIFICATIONS

ITEM	DETAIL
Scan Performance	
Scan Mode	All direction , 24 lines (Automatic continuous scanning)
Indicator	Beeper and LED (stand by: red, good read: green)
Read Rate	2000 scans/sec
Rotate Camera	1±36°
Transfer Rate	Rs232, baudrate: 2400-38400
Resolution	5mil
Depth of Field	up to 230mm @ 13mil
Light Source	650nm ± 10nm visible laser diode
Print Contrast	Above 30% Black
Interface	USB-HID, USB-UART, PS/2, RS232
Decode Type	UPC-A, UPC-E, EAN-13, EAN-8, ISBN/ISSN, Code39, CODABAR, Interleaved 2 of 5, Industrial 2 of 5, Chinese 2 of 5, Code128, Code93, Code11 MSI/PIESSEY, UK/PLESSE, UCC/EAN128, China Postage
Electrical	
Input Voltage	+5V DC, 250mA
Output	1.25W
Power Source	Keyboard wedge, RS-232 or USB from host system
Dustproof and Waterproof	IP54
Illumination	Max. 4800LUX
Environmental	
Operating Temperature	0°C ~ 40°C
Storage Temperature	-10°C ~ 60°C
Humidity	20% ~ 95% RH (non-condensing)
Drop	1.2m drops on the concrete surface
Mechanical	
Dimensions	112mmL x 102mmW x 147mmH
Weight	Approx. 360g
Color Options	White / Black
Cable	2m
Other	
Language	User language support
Interface Type	RJ-45