


# PC CAISSE TACTILE WITH PRIMTER 80mm

Model SK-18.5GB



## Features

- Industrial 18.5" IPS LCD with 50K Lifetime LED Backlight
- Intel® Core® i3 3rd generation dual-core Processor with 4GB DDR3 SDRAM 128GB SSD.
- Supports wide operating temperatures -10~50°C
- IP65 certified front panel protection
- 10 Point Capacitive G+G Touch Screen

senke®

## Introduction

The SK-18.5GB industrial touch panel with a 18.5" IPS LCD screen, low power embedded Intel® Core® i3 3rd Generation dual-core Processor with 4GB DDR3 SDRAM,128GB SSD provides computing performance in a compact system. To enhance its durability, the SK-18.5GB is designed with IP65 front protection, aluminium front bezel and 10 point Capacitive G+G touch screen.It supports wide operating temperatures -10~50°C and includes full size mini-PCIe slot to extend the functionality and meet a variety of automation applications needs.

## Specifications

### General

Certification	CCC,CE, FCC ,ISO9001
Cooling system	Fan
Dimensions	285.5x 460.5 x 54.6 mm
Enclosure front bezel	Front bezel : Aluminum Back housing : cold rolled steel plate
Mounting	Default wall mounting bracket
OS support	Microsoft ® Windows10,64bit
Optional color	Default windows 10 English professional trial Version
Weight (Net)	Silver or black
Weight (Gross)	4.2 kg
Package size	5.5 kg
	53.5 x 36.5 x 15 cm

### System Hardware


CPU	Intel® Core® i3 3rd generation Dual-core Processor
Memory	4GB DDR3
Storage	128GB SSD
Expansion Slots	Full-size Mini PCI-E
LAN	100 Base-T x1

### I/O

COM x2 (RS232)  
Power x1  
HDMI x1  
VGA x1  
USB x4  
LAN x1 (RJ-45 )  
Audio input x1  
Audio output x1  
Customized Interface available

### Drawing

Unit (mm)



### LCD Display


Display type	IPS LCD screen
Display size	231.4 × 410.8 mm (H×V)
Resolution	1920 × 1080
Max. colors	16.7 M
Luminance cd/m²	250
Viewing angle (H/V°)	178°/178°
Backlight life	50000 hrs
Contrast ratio	700:1
Aspect ratio	16:9
Lifespan	36 million touches at single point
Touch type	10 Point Capacitive G+G touch screen
Response	≤5 ms

### Environment

Humidity	10~ 95% RH @ 40°C, non-condensing
Ingress Protection	Front panel: IP65
Operating Temperature	-10 ~ 50°C
Storage Temperature	-30 ~ 70°C

### Accessories

Adaptor (DC 12V) (cable 1 meter)  
Power plug ( cable 1.2 meter )  
Default wall mounting bracket  
8mm thermal printer



Imprimante	Thermique avec papier standard 8cm	Largeur 8cm
	Anti-bourrage	Oui
	Autocoupure	Plus que 7,000,000 cuts
	Détection et alerte fin du papier	Oui
	Capacité du diamètre du rouleau papier	120 millimètres
	Qualité	203dpi