

P3SR

Thermal Receipt Printer



Characteristic

- Compact body, exquisite design
- Side-opening cover, easy for paper loading
- Gear dust proof, long printer life
- Fast printing speed 160 mm/s
- Support multi-language printing
- Support 1D & 2D barcode printing
- A cost-effective printer for entry-level businesses



Gear dust prevention



Error reprint



Provides APP for
different platforms

Specification

Model	P3SR	
Print parameter	Printing Method	Direct Thermal
	Resolution	203 dpi/180 dpi
	Printing Width	72 mm(Default)/48 mm
	Printing Speed	Max.160 mm/s
	Protocol	ESC/POS
Media	Media Type	Continuous thermal receipt/recycled thermal paper
	Media Width	Max.80 mm
	Paper Roll Diameter	Max Φ 80.0 mm
	Paper exit	Front exit
Barcode	1D	UPC-A, UPC-E, EAN-8, EAN-13, CODE39, ITF, CODABAR, CODE128, CODE93
	2D	QR Code,PDF417
Font	Chinese	Simplified /Traditional (24×24)
	Alphanumeric	Font A 12×24,Font B 9×17
	Character Set	Chinese, International Character Sets, Korean, Japanese
Interface	Standard	1*USB Type-B, Ethernet, Cash drawer
	Optional	Wi-Fi, Bluetooth
Beeper	Type	Built-in buzzer, external buzzer (optional)
Sensor	Standard	Over-temperature detection, paper out detection, cover up detection, cutter jam detection
Memory	RAM	4 MB
	Flash	4 MB
Power Supply	Input	AC 100~240 V, 50/60 Hz
	Output	DC 24 V 1.5 A
Software	Driver	Windows 7/8/10, Windows Server 2008/2012/2016 Linux, Javapos, OPOS, MacOS
	Utility	Windows 7/8/10, Windows Server 2008/2012/2016
Reliability	TPH	100 km
	Cutter life	1 million
Environment	Operating temperature	0°C~45°C/25%~85%RH
	Storage temperature	-20°C~60°C/5%~95%RH
Printer Dimension	145 mm×123.5 mm×120.3 mm (L×W×H)	
Certification	CCC, CE, FCC	