



LABEL PRINTER INTEGRATED HANDHELD TERMINAL

5.5-inch HD display · Octa-core processor · Sticker one-piece printing

- 
Android
- 
4G
- 
WIFI
- 
Bluetooth
- 
Sticker print
- 
1D barcode
- 
2D barcode
- 
NFC
- 
PSAM
- 
Camera
- 
GPS



Product Specifications

Performance

Octa Core	
CPU	MT6765X Octa core 64-bit 2.3GHz high-performance processor
RAM+ROM	2GB+16GB/4GB+64GB
Expand memory	Micro SD(TF) Supports up to 256GB
System	Android 10.0/Android 13.0

Data Communication

WLAN	Dual-band 2.4GHz / 5GHz, Support IEEE 802.11ac/a/b/g/n/d/e/h/i/j/k/r/v protocol
WWAN	2G: GSM (850/900/1800/1900mhz)
	3G: WCDMA (850/900/1900/2100mhz)
	4G: FDD:B1/B3/B4/B7/B8/B12/B20 TDD:B38/B39/B40/B41
Bluetooth	Support Bluetooth 5.0+BLE Transmission distance 5-10 meters
GNSS	Support Gps, Galileo, Glonass, Beidou

Physical Specifications

Dimensions	179mm×74.5mm×22.5mm (the thinnest) 49.5mm (the printing part)
Weight	<500g (Depends on device function configuration)
Display	5.5 inch IPS color display with resolution 720×1440
Screen brightness	>500cd/m2
TP	Supports multi-touch
Battery capacity	Rechargeable polymer battery 7.6V 2750mAh (Equal to 3.8V 5500mAh),removable
	Standby time >350 hours
	Charging time 3-4H, Using standard power adapter and data cable
Expansion Card slot	Micro SIM card x 1, TF card x 1, PSAM×2 (Optional)
Communication interface	Type-C USB x 1, OTG
Speaker volume	>93db (test distance 10cm)
Audio	Speaker (mono), Microphone, Receiver
main keys	Home key, Delete key, Back key,Confirm key
Side keys	Silicone keys: Power key, Volume +/- key, Scan key ×2
Sensors	Gravity sensor, Light sensor, Proximity sensor, Vibration motor

Data Collection

Barcode Scanning (Optional)	
2D Scanning engine	Honeywell N5703 N6703 N6703HD,N6602-W2
1D Symbologies	UPC/EAN, Code128, Code39, Code93, Code11, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Codabar, MSI, RSS,etc. Postal Codes:USPS Planet, USPS Postnet, China Post, Korea Post, Australian Postal, Japan Postal, Dutch Postal (KIX), Royal Mail, Canadian Customs,etc.
2D Symbologies	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode, HanXi,etc.

Thermal sticker printer (Standard)

Printing speed	70mm/s
Print points	384 dots
Paper slot	58mm
Paper diameter	35mm
Paper type	Support for Sticker / label Black mark printing

Camera (Standard)

Rear camera	13MP HD camera,Support auto focus, Flash, Anti-shake, Macro shooting
Front camera	2MP color camera

NFC (Optional)

Frequency	13.56MHz
Protocol	Support ISO14443A/B, 15693 agreement
Distance	2cm-5cm

Language/Input Method

Input	English, Pinyin, Handwriting input, Support soft keypad
Language	Language packs in Simplified Chinese, Traditional Chinese, English, Korean, Japanese, Malaysian,etc.

User Environment

Operating temperature	-20℃ - 55℃
Storage temperature	-40℃ - 70℃
Environment humidity	5%RH--95%RH(no condensation)
Drop specification	6 sides Supports 1.2 meters drops on the marble within the operating temperature
Rolling test	0.5m rolling for 6 sides, can still work steadily
Sealing	IP54

Accessories

Standard	Adapter, Data cable, Protective film, Instruction manual
----------	--