

Smart Android POS Terminal

ZQ-1010

HIGHLIGHTS

- 10.1" Capacitive touch panel
- Android system
- Built-in thermal printer
- Camera integration for option
- Multi data ports
- WiFi supported / 3G or 4G optional



SPECIFICATIONS

CPU	Quad-core Rockchip 3288 A17 1.8GHZ,	Thermal Printer	58mm Thermal Printer, Max 60 mm/sec, Diameter Max. $\varnothing$ 60 mm, USB	
RAM	DDR3 2GB		GB2312, PC437, Katakana, PC850, PC860, PC863, PC865, WPC1253, Iran, WPC1256, PC737, WPC1250, WPC1252, PC866, PC852, PC858, , User define	
Storage	NAND Flash 8GB Mini SD 32GB(max) Extendable	Optional Peripherals	MSR	RS232 DC5V $\pm$ 5%, 65mA (max)
WI-FI	Optional 802.11 b/g/n WI-FI module		RFID	RS232 DC5V $\pm$ 5%, 65mA (max)
OS	Android 5.1		IC Card	RS232 DC5V $\pm$ 5%, 65mA (max)
Language	English /Chinese /Russian /French /German /Italian /Spanish	External Port	3 x USB, 1 x TF, 1 x LAN, 1 x DC12V Input, 1 x Cash Drawer, 1 x RS232	
Operator Display	10.1" diagonal, LED Back light, 1024 $\times$ 600, LVDS	Camera (Optional)	0.3MP 2D Barcode scanner	
Touch Screen	10.1" diagonal, Projected Capacitive touch, I2C	Environment	Operating temperature and humidity: -10°C ~ 40°C, 20 ~ 80% RH	
Customer Display	LED 9 Digit, DC5V, RS232, 9600BPS Characters: 0...9		Storage temperature and humidity: -20°C ~ 50°C, 20 ~ 90% RH	
(optional)	LCD 2*20 Digit, DC5V, RS232, 9600BPS; ASCII code	Dimension	276(L) $\times$ 272 (W) $\times$ 95 (H) mm	
Power Supply	DC12V 5A			
Battery (optional)	8.4V 2200mAh			



Customer Display



Multi Ports



Camera (option)



Capacitive Touch Panel