

ZQ-LS6050 II Specifications

Item		Description
Light Source		650nm visible laser diode
Working Distance		30m
Communication		WIFI 2.4GHz
Memory Capacity		64K
Precision		Above 4mil
Error Rate		Less than 1/5million
Print Contrast		Above 30%
Scan Speed		120scans/sec
Decode Capability		UPC-A, UPC-E, EAN-13, EAN-8, ISBN/ISSN, Code39, Codabar, Interleaved 2 of 5, Standard 2 of 5, Code128, Code93, Code11, MSI/PIESSEY, UK/PLESSEY, UCC/EAN128, RSS, China Postal Code.
Depth of Field		20mm-90mm (4mil) ; 30mm-400mm (12mil)
Dimensions		160x65x85mm(LxWxH)
Weight		125g
Depth of Field		70°Hx70°V
Battery		3.7V 750mAh Lithium polymer battery
Input Voltage		5VDC±5%
Current	Working Current	50mA
	Standby Current	30mA
Humidity		5% ~ 95%RH(non-condensing)
Operating Temperature		-10°C ~ 60°C
Operating Temperature		-20°C ~ 60°C
Dustproof and Waterproof		IP42
ESD Protect		15KV
Drop Test		1.5m drops on the concrete surface

