

WavePOS 68



Ready in Windows System



True Flat Screen



VFD Easy Installation



Hard Disk
Quick Maintenance



2nd LCD Display

System

CPU Support	Intel® Celeron® Bay Trail J1900 Processor (up to 2.42 GHz)
Memory	Support up to 8GB DDR3L
Core Logic	Intel® Bay Trail
Network	10/100/1000 Base-T Gigabit Ethernet
Power Supply	12V Power Adaptor
System Weight	5.8 kgs
Dimension	384 x 324 x 194 mm (WxHxD)
OS	POSReady 7, Windows 7, Windows 8, Windows 10

Display

LCD	15" TFT LCD Panel
Max. Resolution	1024 x 768
Brightness	300 nits
Touch Screen	PCAP Multitouch Screen

Storage

HDD	1 x 2.5" SATA HDD
SSD	SSD SATA Interface Max. 1 TB

Environmental


Operating Condition	0°C ~ 40°C, 20% RH ~ 80% RH
Storage Condition	-20°C ~ 60°C, 10% RH ~ 90% RH

Safety







Safety Standards	CCC / CE / FCC
------------------	----------------

I/O Ports








Serial Ports	3 x External COM (RJ Type, w / +5V / 12V Power Selectable)
USB Ports	3 x External 2.0 USB Ports 1 x External 3.0 USB Port
Ethernet	1 x 10 / 100 / 1000 Mbps (RJ45)
VGA	1 x DB-15 VGA Interface
Cash Drawer	1 x RJ11 (12V)
DC-IN	12V DC-IN
Power Switch	1 x Power Switch



Features

-  Industrial LCD Panel
-  Multi-touch Panel
-  Fanless System Design
-  Intel® CPU
-  Industrial Circuit & Components
-  Aluminium Stand

Option Peripherals

-  2nd LCD Monitor
-  Magnetic Stripe Card Readers
-  Customer Display
-  Barcode Scanner
-  Thermal Printer
-  QR Code Scanner
-  Finger Printer