



# SMART POS SERIES

## ZQ-P1088 Mid

### HIGHLIGHTS

- Main housing made by Aluminum
- Built-in 80mm Seiko mechanism thermal printer
- Various options of peripherals
- Fanless design
- Operator display angles adjustable

### Optional

- MSR/Dallas key/RFID

## SPECIFICATIONS

Model		ZQ-P1088 Mid	
CPU	Intel® Bay-Trail J1900 Quad Core	Audio	Interface x 1
Memory	1 x DDR3 4GB	VGA	1 x DB-15 VGA Interface
Network	RTL8168DE PCI-E Gigabit Ethernet NIC	HDMI	N/A
Power Supply	100-240V/ 3.5A 47~63Hz	DISPLAY	
Video Card	Intel Graphics Media	Viewing Angle	85 degree adjustable
Sound Card	Accelerator3150(256MB/Intel)	LCD	12" TFT LCD
	RTL ALC662 @INTEL 82801G(ICH7)High Definition Audio	Max. Resolution	1024 x 768
Dimension	290x225x360	Touch Screen	5-wires resistive 20,000,000 times touch life
O.S. Compliant	VISTA/WIN7/WIN8/WIN10(optional)	ENVIRONMENT	
SSD	64GB SSD	Operation Temperature	0~40℃
I/O PORTS		Storage Temperature	-40~50℃
USB	4 x USB 2.0 port	Humidity	38~80%℃
Serial Port	3 x DB-9 RS232		
LAN	1 x 10/100/1000 Mbps		



Resistive Touch Panel and LCD Adjustable



Customer Display



Optional MSR



Optional I-button



Various interfaces