


Touch all in one PC

Model SK-21.5G



SIZE CONFIGURATION TABLE



Features

- 21.5" IPS LCD with 50K Lifetime LED Backlight
- Intel® Core® i3 3rd generation dual-core Processor with 4GB DDR3 SDRAM 128GB SSD.
- Supports wide operating temperatures -10~50°C
- IP65 certified front panel protection
- 10 Point Capacitive G+G Touch Screen

Introduction

The SK-21.5GB Kios all in one pc with a 21.5" IPS LCD screen, low power embedded Intel® Core® i3 3rd Generation Dual-core Processor with 4GB DDR3 SDRAM,128GB SSD provides computing performance in a compact system. To enhance its durability, the SK-21.5GB is designed with IP65 front protection, aluminium front bezel and 10 point Capacitive G+G touch screen.It supports wide operating temperatures -10~50°C and includes full size mini-PCIe slot to extend the functionality and meet a variety of automation applications needs.

Specifications

General

Certification	CCC,CE, FCC ,ISO9001,BIS,CCC
Cooling system	Fan
Dimensions	349.3 x 559 x 85.5 mm
Enclosure front bezel	Front bezel : Aluminum Back housing : Cold rolled steel plate
Mounting	Default wall mounting bracket Microsoft ® Windows10,64bit
OS support	Default windows 10 English professional trial Version
Optional color	Silver or black
Weight (Net)	6 kg
Weight (Gross)	7.5 kg
Package size	63.5 x 43.5 x 14.5 cm

LCD Display

Display type	IPS LCD screen
Display size	269.1 × 477.6 mm (H×V)
Resolution	1920 × 1080
Max. colors	16.7 M
Luminance cd/m²	250
Viewing angle (H/V°)	178°/178°
Backlight life	50000 hrs
Contrast ratio	1500:1
Aspect ratio	16:9
Lifespan	36 million touches at single point
Touch type	10 Point Capacitive G+G touch screen
Response	≤5 ms

System Hardware

CPU	Intel® Core® i3 3rd generation Dual-core Processor
Memory	4GB DDR3
Storage	128GB SSD
Expansion Slots	Full-size Mini PCI-E
LAN	100 Base-T x1

Environment

Humidity	10~ 95% RH @ 40°C, non-condensing
Ingress Protection	Front panel: IP65
Operating Temperature	-10 ~ 50°C
Storage Temperature	-30 ~ 70°C

Accessories

- Adaptor (DC 12-19V) (cable 1 meter)
- Power plug (cable 1.2 meter)
- K type bracket

I/O

- Power x1
- HDMI x1
- VGA x1
- USB x4
- LAN x1 (RJ-45)
- Audio input x1
- Audio output x1
- Other customized Interface available

SUPPORT MULTIPLE INFORMATION CHECKING SYSTEM

Floor guide, System management, Information query, Traffic query, etc.



10 POINT SENSITIVE TOUCH

Sensitive multiple touch, Support multiple gesture, Easily to reach



REMOTE OPERATION

