

# Touch all in one PC

Model SK-32G

SIZE CONFIGURATION TABLE



## Features

- 32" IPS LCD with 50K Lifetime LED Backlight
- Intel® Core® i3 3rd generation dual-core Processor with 4GB DDR3 SDRAM 128GB SSD.
- Supports wide operating temperatures -10~50°C
- IP65 certified front panel protection
- 10 Point Capacitive Touch Screen

## Introduction

The SK-32G Kios all in one pc with a 32" IPS LCD screen, low power embedded Intel® Core® i3 3rd Generation Dual-core Processor with 4GB DDR3 SDRAM,128GB SSD provides computing performance in a compact system. To enhance its durability, the SK-32G is designed with IP65 front protection, aluminium front bezel and 10 Point Capacitive Touch Screen.It supports wide operating temperatures -10~50°C and includes full size mini-PCIe slot to extend the functionality and meet a variety of automation applications needs.

## Specifications

### General

<b>Certification</b>	CCC,CE, FCC ,ISO9001,BIS,CCC
<b>Cooling system</b>	Fan
<b>Dimensions</b>	74.39*6.17*43.96CM
<b>Enclosure front bezel</b>	Front bezel : Aluminum Back housing : Cold rolled steel plate
<b>Mounting</b>	Default wall mounting bracket Microsoft ® Windows10,64bit
<b>OS support</b>	Defult windows 10 English professional trial Version
<b>Optional color</b>	Silver or black
<b>Weight (Net)</b>	8.6 kg
<b>Weight (Gross)</b>	10.2 kg
<b>Package size</b>	82*12.1*55.2CM

### LCD Display

<b>Display type</b>	IPS LCD screen
<b>Display size</b>	393.3 × 698.7 mm (H×V)
<b>Resolution</b>	1920 × 1080
<b>Max. colors</b>	16.7 M
<b>Luminance cd/m<sup>2</sup></b>	250
<b>Viewing angle (H/V°)</b>	178°/178°
<b>Backlight life</b>	50000 hrs
<b>Contrast ratio</b>	1500:1
<b>Aspect ratio</b>	16:9
<b>Lifespan</b>	36 million touches at single point
<b>Touch type</b>	10 Point Capacitive G+G touch screen
<b>Response</b>	≤5 ms

### System Hardware

<b>CPU</b>	Intel® Core® i3 3rd generation Dual-core Processor
<b>Memory</b>	4GB DDR3
<b>Storage</b>	128GB SSD
<b>Expansion Slots</b>	Full-size Mini PCI-E
<b>LAN</b>	100 Base-T x1

### Environment

<b>Humidity</b>	10~ 95% RH @ 40°C, non-condensing
<b>Ingress Protection</b>	Front panel: IP65
<b>Operating Temperature</b>	-10 ~ 50°C
<b>Storage Temperature</b>	-30 ~ 70°C

### I/O

Power	x1
HDMI	x1
VGA	x1
USB	x4
LAN	x1 (RJ-45 )
Audio input	x1
Audio output	x1
Other customized Interface available	

### Accessories

Power plug ( cable 1.2 meter )
K type bracket

## 10 POINT SENSITIVE TOUCH

Sensitive multiple touch,Support multiple gesture.Easily to reach



## SUPPORT MULTIPLE INFORMATION CHECKING SYSTEM

Floor guide, System management, Information query, Traffic query, etc.



## REMOTE OPERATION

