

AIO INDUSTRIAL COMPUTER

Model SK-24GB



Features

- Industrial 24" IPS LCD with 50K Lifetime LED Backlight
- Intel® Core®i5 2.4GHz dual-core Processor with 8GB DDR3 SDRAM 128GB SSD.
- Supports wide operating temperatures -10~50°C
- IP65 certified front panel protection
- 10 Point Capacitive G+G Touch Screen

senke®

Introduction

The SK-24GB industrial touch panel pc with a 24" IPS LCD screen, low power embedded Intel® Core®i5 2.4GHz dual-core Processor with 8GB DDR3 SDRAM,128GB SSD provides computing performance in a compact system. To enhance its durability, the SK-24GB is designed with IP65 front protection, aluminium front bezel and 10 point Capacitive G+G touch screen.It supports wide operating temperatures -10~50°C and includes full size mini-PCIe slot to extend the functionality and meet a variety of automation applications needs.

Specifications

General

Certification	CCC,CE, FCC ,ISO9001
Cooling system	Fan
Dimensions	345.3x571.8x55.1 mm
Enclosure front bezel	Front bezel : Aluminum Back housing : cold rolled steel plate
Mounting	Default wall mounting bracket
OS support	Microsoft ® Windows10,64bit Default windows 10 English professional trial Version
Optional color	Black
Weight (Net)	6.5 kg
Weight (Gross)	8 kg
Package size	66 x 45 x 15 cm

LCD Display

Display type	IPS LCD screen
Display size	293.2 × 521.2 mm (H×V)
Resolution	1920 × 1080
Max. colors	16.7 M
Luminance cd/m²	250
Viewing angle (H/V°)	178°/178°
Backlight life	50000 hrs
Contrast ratio	1500:1
Aspect ratio	16:9
Lifespan	36 million touches at single point
Touch type	10 Point Capacitive G+G touch screen
Response	≤5 ms

System Hardware

CPU	Intel® Core® i5 2.4GHz dual-core Processor
Memory	8GB DDR3
Storage	128GB SSD
Expansion Slots	Full-size Mini PCI-E
LAN	100 Base-T x1

Environment

Humidity	10~ 95% RH @ 40°C, non-condensing
Ingress Protection	Front panel: IP65
Operating Temperature	-10 ~ 50°C
Storage Temperature	-30 ~ 70°C

Accessories

- Adaptor (DC 12V) (cable 1 meter)
- Power plug (cable 1.2 meter)
- Default wall mounting bracket

I/O

- COM x2 (RS232)
- Power x1
- HDMI x1
- VGA x1
- USB x4
- LAN x1 (RJ-45)
- Audio input x1
- Audio output x1
- Other customized Interface available

Drawing

Unit (mm)

