

PRODUCT FEATURES

- Aluminum housing design. Fan-less design.
- Customized mainboard with few cable connections. The inside is very neat.
- Rotatable and inseparable cable cover.
- Easy to add customer display or secondary monitor.
- Peripheral connection cables could easily go through the base and be fixed well.
- Pluggable Dallas Lock / MSR modules without cable connection.



Excellent Heat Sinking



Extendable Peripheral Port



Multi-ports Available



Rotatable Cable Cover

SPECIFICATIONS

CPU	Intel 4210U Core i5, 1.7GHz up to 2.7GHz	Customer Display	VFD or 9.7" secondary monitor (option)
Graphics	Intel HD Graphics 4400	I/O Ports	2 x USB3.0,
Graphic Output	VGA, HDMI, LVDS,EDP		6 x USB2.0
Display	15" TFT LCD, 1024 x 768 (max.)		1 x LAN
Viewing Angle	45 degree adjustable		1 x VGA
Touch Solution	15" Capacitive touch panel		1 x HDMI
RAM	DDR3L 1333/1600MHz, 4GB as standard,		1 x MIC-IN, 1 x LINE-OUT
	optional up to 16GB, 2XSO-DIMM		1 x DC12V_OUT
Storage	64GB SSD as standard, optional up to 256GB,		2 x RS232
	1 x SATA, 1 x M-SATA	O.S. Compliant	Windows 8, Windows 10, Linux (not included)
Audio	Realtek ALC 662HD (on board)	Input Power	Ø2.5 x DC12V
LAN	Realtek RTL8111H, 1000M (on board)	Power Supply	100 ~ 240V / 47 ~ 63Hz
Extended Slots	1 x MINI-PCIE (for 4G/WIFI), 1 x SIM (on board)	Work Environment	-10 ~ 60 degrees, 0% ~ 95%

